

## NOISELESS ABSORPTION MINIBAR DOMETIC HIPRO 3000



### GENERAL

- Noiseless absorption cooling
- Lowest Energy consumption for absorption minibars
- Fuzzy Logic energy saving system
- Patented CUC cooling unit control system
- Automatic defrost
- Infrared sensor controlled LED interior light
- Remote control temperature adjustment
- Certified according to ISO 9001 and 14001
- Made in Germany

### DATA

<b>Model class:</b>	30 liter
<b>Dimensions (H x W x D):</b>	527 x 388 x 418 mm (built-in)
<b>Weight:</b>	13 kg
<b>Energy consumption:</b>	0.57 kWh/24h
<b>Energy efficiency index:</b>	C
<b>Cabinet:</b>	Anthracite Black
<b>Door:</b>	Integrated handle Magnetic door seal
<b>Features:</b>	Two height adjustable shelves One height adjustable door rack for bottles One height adjustable door rack for mini bottles and snack items

### OPTIONS

- Lock
- LED-Door opening indicator
- Infrared Remote control for temperature adjustment

## VENTILATION OF THE COOLING UNIT

To ensure optimum cooling performance with minimum energy consumption, several basic principles need to be followed when installing an absorption miniBar. The heat which the cooling unit extract from the refrigerator interior is emitted at the back of the miniBar. There must be sufficient ventilation here to prevent a built-up of heat. The free ventilation space for incoming and outgoing air should be at least 200 cm<sup>2</sup>. The distance from the rear of the miniBar to the rear wall of the furniture must be at least 2 cm. When installing the miniBar, ensure that it is standing on a stable and horizontal surface, and not directly near a heat source.

Outgoing air (warm) Incoming air (ambient)

